





FIRE RATED SILICONE TEARDROP GASKET & EDGE-SEAL MATERIALS FOR FIRE DOORS

DESIGNED FOR SIMPLE INSTALLATION & MAXIMUM PROTECTION

Door systems using gaskets made from our fire rated silicone material have been tested and classified to UL 10B and UL 10C.

Gasket systems using our fire rated silicone have also been tested to Category H Smoke and Draft Control Gasket for use with:

- Classified wood core doors rated 20 minute fire tested without hose stream
- Wood or plastic covered composite type fire doors rated up to and including 1.5 hours
- Hollow metal steel or steel covered composite type doors rated up to and including 3 hours



UL File R25667

Profile: standard shape or custom profile

Material: 75 durometer (dense) silicone with adhesive

Packaging: 300' p/box or cut to desired length

Color Options: brown, light brown, black, light grey, white and clear

Seal System Benefits

- Excellent air/smoke seal
- Door Systems tested & approved to UL 10B & UL 10C
- Door Systems tested & approved to Smoke and Draft Control - UL Classified Category H
- Door Systems tested & approved to Edge Sealing System - UL Classified Category G

Seal System Applications

- Hotels
- Schools
- Commercial Buildings
- Libraries
- Public Buildings
- Government Buildings



Scan the QR Code to Contact Us

