

Cleaning Recommendations
for AIRFLOOR® / AIRFLEX®



Airflex® / Airfloor® is an easy to clean silicone floor covering for aircrafts. It is usually installed in galleys, lavatories and entrance areas protecting the cabin floor from corrosion.

Airflex® / Airfloor® is resistant to typical contaminants such as cleaners, cosmetics, bodily fluids, organic acids, food and beverages.

CLEANING

- Regular cleaning
- Cleaners recommended by the airframe manufacturer are suitable (e.g. ABD0007).
- Water based solutions with corrosion inhibitors and low alkalinity are preferred.
- For general use “**Imi Top**” (fulfils the requirements of AM 1550B, Boeing D6-17487 and Douglas Aircraft Company CSD#1)
For sanitary area “**Into top**” (fulfils AMS 1550B)
- In case of normal soiling use cleaner in a low concentration.
- For heavy contamination, a higher concentration or undiluted solution may be necessary.
- To avoid streaks wipe with water after cleaning.
- For stain removal, brush with a soft plastic brush, wipe with water and dry.
- Pay heed to the cleaner manufacturer’s recommendations.
- Avoid pure abrasive solvents, alcohol, acetic acid and caustic chemicals.

Prepared: Bormuth	Date of first Issue: 15.12.00	Released: Glatter:17.12.03	Issue: Issue 5	Date: 25.09.12	Changed / Date:: Möller / 03.12.12	Print Date: 25.03.13
----------------------	----------------------------------	-------------------------------	-------------------	-------------------	---------------------------------------	-------------------------