

Cleaning Recommendations
for DUROFLEX®



DUROFLEX® is an easy to clean floor covering for aircrafts. It is usually installed in galleys, lavatories and entrance areas protecting the cabin floor from corrosion. DUROFLEX® is resistant to typical contaminants such as cleaners, cosmetics, bodily fluids, organic acids, food and beverages.

CLEANING

- Regular cleaning
- Cleaners recommended by the airframe manufacturer are suitable (e.g. ABD0007).
- Water based solutions with corrosion inhibitors and low alkalinity are preferred.
- For general use “**Imi Top**” (fulfils the requirements of AM 1550B, Boeing D6-17487 and Douglas Aircraft Company CSD#1)
For sanitary area “**Into top**” (fulfils AMS 1550B)
- In case of normal soiling use cleaner in a low concentration.
- For heavy contamination, a higher concentration or undiluted solution may be necessary.
- To avoid streaks wipe with water after cleaning.
- For stain removal, brush with a soft plastic brush, wipe with water and dry.
- Pay heed to the cleaner manufacturer’s recommendations.
- Avoid pure abrasive solvents, alcohol, acetic acid and caustic chemicals.

Prepared: Bormuth	Date of first Issue: 20.07.2012	Released: G. Cluett: 20.07.2012	Issue: Issue 2	Date: 25.09.2012	Changed / Date: Möller / 03.12.2012	Print Date: 26.03.13
----------------------	------------------------------------	------------------------------------	-------------------	---------------------	--	-------------------------